

# SENSIT<sup>®</sup> GOLD 3

MULTI GAS DETECTOR

WORKER & COMMUNITY SAFETY

LOCATE ABOVE & BELOW GROUND LEAKS



GPS &  
Datalogging

Rechargeable  
Battery

Flashlight  
Feature

Rubberized  
Housing

Two Speed  
Pump

**FAST  
DETECTION  
TO AS LITTLE  
AS 5 PPM!**



# METHANE GAS CONVERSION

% GAS	% LEL	PPM	% GAS	% LEL	PPM
-	0.1	50	2.0	40.0	20,000
-	0.2	100	2.5	50.0	25,000
-	1.0	500	3.0	60.0	30,000
0.1	2.0	1,000	3.5	70.0	35,000
0.5	10.0	5,000	4.0	80.0	40,000
1.0	20.0	10,000	4.5	90.0	45,000
1.5	30.0	15,000	5.0	100.0	50,000

# LED DOME ALARM COLORS

COLOR	INDICATION
Solid Green	Ready
Flashing Green	Low Battery Indication
Solid Yellow	Low Condition For Combustible Gas (5% - 9.9% LEL)
Solid Red	Potentially Hazardous for Combustible Gas (10 to 49.9% LEL)
Flashing Red +Audible Alarm	Alarm Condition, Sensor Failure Or Flow Block >50% LEL Combustible Gas CO - 35 PPM, H2S - 10PPM, O2 - <19.5% or > 23.5%
Solid Blue	Busy, User In Menus, Calibration, Smart-link 360 Viewing Logs

**FLASHLIGHT**

**LEL/PPM SENSOR**

**TICK WHEEL**

**3 BUTTON OPERATION**

A	B	C
Power On/Off	Access Menu for Tick	Save Data
Mute	Barhole	Autozero
Activate Smart-Cal	Leak Search	Scroll Through Menu Items
Escape Menu	Purge	Activate Flashlight
	Other Special Modes	

Learn more at [gasleaksensors.com](http://gasleaksensors.com)